



## The Q210d is an extremely powerful compact monitor.

Although perfectly suited to soffit mounting, the Q210d's compact dimensions and rotate-able mid-hi baffle make it ideal as a mid-field monitor when main monitor performance is required. It may be used in isolation or combined with the QSB1118 sub-woofer, a perfect choice for 5.1 / 6.1 installations.

The monitors are supplied with a separate dedicated electronics package, 19" rack mounting power amplifiers and electronic crossover / loudspeaker management system.

Applications: Soffit mounted or free standing main monitor



# Q210d

### Specifications

Size (WxHxD) Mounted Horizontally	590(w) x 850(h) x 355(d) mm
Size (WxHxD) Mounted Vertically	850(w) x 590(h) x 355(d) mm
Weight	70 kgs
Drivers	Bass cone: 2 x 254 mm (10") Midrange: 1 x 75mm (3") High Frequency 1 x 28mm (1")
Maximum SPL	123dB at 1m
Frequency Response	38Hz - 20KHz +/- 2 dB

### Input

Connector	1 x twin-pair gold plated binding posts accept bare ends or 4mm banana plugs
Amplifier power	Bass 1250 W RMS into 4 Ohms Mid 450 W RMS into 8 Ohms High 450W RMS into 8 Ohms
High Crossovers	Linkwitz-Riley 4k5Hz, 24dB/oct
Low Crossover point	Linkwitz-Riley 450Hz, 24dB/oct

### Electronics (Stereo Pair)

Amplifier	2 x AP800 & 1 x AP1300 (see AP800/AP1300 specification)
Crossover	1 x SM748 (see SM748 specification)

