

QUESTED VH2108

Near-Field Passive Reference Monitor



QUESTED



A 2-way passive design with Quested's world-famous 200mm (8") high excursion bass driver.

The VH2108 is the outcome of Quested listening to customers. A Post-Production facility in New York wanted to standardise the monitoring in all of their rooms, after extensive listening tests they settled on the H108.

Then they asked if it was possible to extend the low frequency response. An amplifier module in a VS2108 was replaced with a passive crossover network from a H108, the cabinet was retuned, and the VH2108 was born.

Some typical applications include Post facilities, project/home studios, components in multi channel systems.

We recommend a Quested AP800 amplifier for use with the VH2108.

Size (WxHxD)	337(w) x 400(h) x 340(d) mm
Weight	19 kgs
Drivers	Bass cone - 1 x 200 mm (8") High Frequency soft dome - 1 x 28mm (1 1/8")
Maximum SPL	111 dB (C)
Sensitivity	90.5 dB at 1W at 1m
Frequency Response	50Hz - 20kHz +/-2 dB
Input Connector	Dual pair gold plated binding posts for bi-wiring
Nominal Impedance	8 ohm
Crossovers	Multi-pole network utilizing polypropylene capacitors and air cored inductors throughout
Power requirements	Amplifier rated at 8 ohms between 60 and 200W RMS per channel
Options	Cloth covered grill and magnetic shielding

Quested Monitoring Systems

Unit 8, Kingsgate, Heathpark, Honiton, Devon EX14 1YG, UK - T +44 (0)1404 41500 - E info@quested.com

www.quested.com



EAT



SLEEP



MIX